

| | | | | | | | | | | | | |
|-----------------------------|--------|--------------------|-----------------------|------------|--------|--------|---------------|------------------|-----------|-------------|----------|------|
| THE KEYFLEX COMPANY PTY LTD | | General Tolerances | | | | | | (Revision): | | A3 | | |
| | | | | | | | | (Date): | | 10/06/2004 | | |
| (File No.): | | | | | | | | (File Type) : | (Control) | | (Page): | 1of1 |
| | | | | | | | | | | | | |
| (Unit): (mm) | | | | | | | | | | | | |
| (Base Dimension) | | (Tolerance) | | | | | | (Base Dimension) | | (Tolerance) | | |
| (Over) | (Over) | (Rubber) | (Mould/Adhesive act.) | (Hardware) | (Hole) | (Pole) | (Packing box) | (Over) | (Over) | (Plastic) | (Remark) | |
| | 3 | ±0.07 | ±0.01 | ±0.05 | +0.10 | -0.10 | ±0.50 | 0 | 3 | ±0.07 | | |
| 3 | 6 | ±0.09 | ±0.01 | ±0.06 | +0.12 | -0.12 | ±0.60 | 3 | 6 | ±0.08 | | |
| 6 | 10 | ±0.11 | ±0.02 | ±0.08 | +0.15 | -0.15 | ±0.75 | 6 | 10 | ±0.10 | | |
| 10 | 18 | ±0.14 | ±0.02 | ±0.09 | +0.15 | -0.18 | ±0.90 | 10 | 14 | ±0.11 | | |
| 18 | 30 | ±0.17 | ±0.02 | ±0.11 | +0.21 | -0.21 | ±1.05 | 14 | 18 | ±0.12 | | |
| 30 | 50 | ±0.20 | ±0.03 | ±0.13 | +0.25 | -0.25 | ±1.25 | 18 | 24 | ±0.13 | | |
| 50 | 80 | ±0.23 | ±0.03 | ±0.15 | +0.30 | -0.30 | ±1.50 | 24 | 30 | ±0.15 | | |
| 80 | 120 | ±0.27 | ±0.04 | ±0.18 | +0.35 | -0.35 | ±1.75 | 30 | 40 | ±0.16 | | |
| 120 | 180 | ±0.32 | ±0.04 | ±0.20 | +0.40 | -0.40 | ±2.00 | 40 | 50 | ±0.18 | | |
| 180 | 250 | ±0.36 | ±0.05 | ±0.23 | +0.46 | -0.46 | ±2.30 | 50 | 65 | ±0.2 | | |
| 250 | 315 | ±0.41 | ±0.05 | ±0.26 | +0.52 | -0.52 | ±2.60 | 65 | 80 | ±0.23 | | |
| 315 | 400 | ±0.45 | ±0.05 | ±0.29 | +0.57 | -0.57 | ±2.85 | 80 | 100 | ±0.26 | | |
| 400 | 500 | ±0.49 | ±0.06 | ±0.32 | +0.63 | -0.63 | ±3.15 | 100 | 120 | ±0.29 | | |
| 500 | 630 | ±0.55 | ±0.07 | ±0.35 | +0.70 | -0.70 | ±3.50 | 120 | 140 | ±0.33 | | |
| 630 | 800 | ±0.63 | ±0.08 | ±0.40 | +0.80 | -0.80 | ±4.00 | 140 | 160 | ±0.36 | | |
| 800 | 1000 | ±0.70 | ±0.09 | ±0.45 | +0.90 | -0.90 | ±4.50 | 160 | 180 | ±0.39 | | |
| 1000 | 1250 | ±0.83 | ±0.11 | ±0.53 | +1.05 | -1.05 | ±5.25 | 180 | 200 | ±0.42 | | |
| 1250 | 1600 | ±0.98 | ±0.13 | ±0.63 | +1.25 | -1.25 | ±6.25 | 200 | 225 | ±0.46 | | |
| 1600 | 2000 | ±1.15 | ±0.15 | ±0.75 | +1.50 | -1.50 | ±7.50 | 225 | 250 | ±0.49 | | |
| 2000 | 2500 | ±1.40 | ±0.18 | ±0.88 | +1.75 | -1.75 | ±8.75 | 250 | 280 | ±0.54 | | |
| 2500 | 3150 | ±1.65 | ±0.21 | ±1.05 | +2.10 | -2.10 | ±10.50 | 280 | 315 | ±0.58 | | |
| / | / | / | / | / | / | / | / | 315 | 355 | ±0.64 | | |
| / | / | / | / | / | / | / | / | 355 | 400 | ±0.70 | | |
| / | / | / | / | / | / | / | / | 400 | 450 | ±0.78 | | |
| / | / | / | / | / | / | / | / | 450 | 500 | ±0.84 | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |